

YB5-20 Series

RoHS



产品主要特性 General Characteristics

- 宽输入范围 85Vac ~ 305Vac@YB5
- 4000Vac 隔离耐压
- 工作壳温 -25~+95℃
- 输出短路保护、自恢复
- EMC 符合 EN55032
- Wide Input 85~305Vac@YB5
- I/O-isolation 4000Vac
- Case Temperature: -25~+95℃
- Output Short-circuit Protection, Self recovery
- EMC Meets requirements of Standard EN55032

产品选型表 Model Selection Guide

型号 Product Model	输入电压范围 (标称值) Input Voltage Range (Typical)	输出电压 Output Voltage (Vdc)	输出电流 Output Current (A)	典型效率 Efficiency (%)
YBS5-3W	85~305Vac (100~430Vdc)	3.3	1.25	74
YBS5-5 W		5	1	78
YBS5-9 W		9	0.55	78
YBS5-12 W		12	0.42	80
YBS5-15 W		15	0.33	82
YBS5-24 W		24	0.23	83
YBS10-3 W	85~265Vac (100~375Vdc)	3.3	2	71
YBS10-5 W		5	2	80
YBS10-12 W		12	0.83	81
YBS10-15 W		15	0.67	82
YBS10-24 W		24	0.42	83
YBS15-3 W		3.3	3	74
YBS15-5 W	5	3	76	
YBS15-12 W	12	1.25	80	
YBS15-15 W	15	1	81	
YBS15-24 W	24	0.63	82	
YBS20-3 W	3.3	4	77	
YBS20-5 W	5	4	80	
YBS20-12 W	12	1.67	82	
YBS20-15 W	15	1.33	83	
YBS20-24 W	24	0.83	85	

封装尺寸和管脚定义图 Outline Diagram And Pin Out

